


STARBORN®

CAP-TOR® xd

Color Matched Screws for Composite and PVC Decking



CAP-TOR xd COLOR		DECKING BRAND COLOR		
		AZEK	DECKORATORS	TIMBERTECH
	#31 TAN-GRAY	WEATHERED TEAK	COSTA	
	#34 BROWN	ENGLISH WALNUT MAHOGANY	BOULDER MESA	BROWN OAK DARK ROAST DARK TEAK
	#37 GRAY	CASTLE GATE COASTLINE	GLACIER SALTWATER	ASHWOOD DRIFTWOOD MARITIME GRAY SEA SALT GRAY SILVER MAPLE STONE ASH
	#43 ASHWOOD			WHITEWASH CEDAR BOARDWALK
	#53 DARK GRAY		RIDGELINE SIERRA	
	#54 WARM GRAY	SLATE GRAY TIMBER GRAY	SHORELINE TUNDRA	RECLAIMED CHESTNUT WEATHERED OAK
	#55 DARK SLATE		SLATE	
	#62 SAHARA	TOASTED WHEAT		NATURAL WHITE OAK
	#63 BUCKSKIN			ANTIQUE LEATHER TIGERWOOD COCONUT HUSK
	#64 SAND	BROWNSTONE FRENCH WHITE OAK	CLIFFSIDE	
	#65 ROSY BROWN		SANDBAR	PECAN
	#71 CHOCOLATE	AMERICAN WALNUT DARK HICKORY KONA	KYAYA PATHWAY	DARK COCOA ESPRESSO
	#73 JAVA			DARK OAK MOCHA RUSTIC ELM
	#81 CEDAR		SEDONA	CYPRESS



CAP-TOR[®] xd

Color Matched Screws for Composite and PVC Decking

<p>1. Star Drive Favored by professionals; extra deep recess reduces cam-out.</p>		<p>1. Star Drive Favorecido por los profesionales; El rebaje extra profundo reduce la salida de la leva.</p>
<p>2. Undercut Head Cleanly penetrates the hard outer layer of capstock decking.</p>		<p>2. Undercut Head Penetra limpiamente la capa exterior dura de la plataforma de capstock.</p>
<p>3. Reverse Thread Prevents mushrooming and other surface defects.</p>		<p>3. Reverse Thread Previene la formación de hongos y otros defectos superficiales.</p>
<p>4. Tri-Lobe Shank and Acute Thread Angle For increased driving power and cleaner penetration through harder decking materials.</p>		<p>4. Tri-Lobe Shank and Acute Thread Angle Para una mayor potencia de conducción y una penetración más limpia a través de materiales de cubierta más duros.</p>
<p>5. Type 17 Auger Tip For faster, easier entry; helps prevent splitting.</p>		<p>5. Type 17 Auger Tip Para una entrada más rápida y fácil; ayuda a prevenir la división.</p>
<p>Depth Setter Compatible Collated available</p>		<p>Compatible con medidor de profundidad Compaginado disponible</p>

Installation	Instalación
<p>Install flush with decking surface. Do not overdrive.</p>	<p>Instale al ras con la superficie de la terraza. No conduzca en exceso.</p>
<p>Install two screws per joist.</p>	<p>Instale dos tornillos por viga.</p>
<p>Predrilling is recommended when fastening within 1" from the end of a deck board.</p>	<p>Se recomienda perforar previamente cuando se fija dentro de 1" desde el extremo de una tabla de plataforma.</p>
<p>Recommended: For a clean and professional finish use the SMART-BIT[®] Depth Setter Tool in combination with screws.</p>	<p>Recomendado: Para un acabado limpio y profesional, use la herramienta de ajuste de profundidad SMART-BIT[®] en combinación con tornillos</p>

